

# Technical Data Sheet

## DIVINOL SYNTHOLIGHT HC-FE 5W-30

### Description:

**DIVINOL SYNTHOLIGHT HC-FE 5W-30** is a smooth-running engine oil made by use of the most advanced HC synthesis technology.

It is based on additives with low ash content (low-saps) for application in the most modern spark-ignition and diesel engines.

Due to the HC synthesis technology, **DIVINOL SYNTHOLIGHT HC-FE 5W-30** has a significantly lower evaporation propensity which has a positive effect on oil consumption. The viscosity class 5W-30 guarantees on the one hand a rapid oil circulation of the engine also with low temperatures and on the other hand a sufficiently thick lubricating film with temperatures of up to 160 C°.

Also suitable for LPG/CNG motors. According to the manufacturer's instructions!

### Specifications:

API SN/CF

ACEA A3-04/B4-04/C3-08

### Approvals:

MB-Approval 229.51

Corresponds to the performance requirements of the following manufacturers:

VW 502.00 / 505.00 / 505.01

GM/Opel dexos 2

BMW Longlife-04

Ford WSS M2C-917-A

Fiat 9.55535-S2

### Nominal values

Density/15 °C	Kg/m <sup>3</sup>	853	DIN 51 757
Viscosity/40 °C	mm <sup>2</sup> /s	67	DIN 51 562
Viscosity/100 °C	mm <sup>2</sup> /s	11,5	DIN 51 562
Viscosity index		>165	DIN ISO 2909
Flash point	°C	>220	DIN ISO 2592
Pour point	°C	<-35	DIN ISO 3016

07/11-49260-15 Page 1 of 2

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



ZG Division  
Divinol  
Lubricants + Release Agents

Zeller + Gmelin GmbH & Co. KG  
Schlossstraße 20 · D 73054 Eisligen/Fils  
Phone +49 7161 802-0 Fax +49 7161 802-330

[www.zeller-gmelin.de](http://www.zeller-gmelin.de) [info@zeller-gmelin.de](mailto:info@zeller-gmelin.de)



# Technical Data Sheet

## Application:

**DIVINOL SYNTHOLIGHT HC-FE 5W-30** meets the high performance and quality level for modern spark-ignition and diesel engines. Particularly, this oil guarantees the extremely long-lasting efficiency of the subsequent exhaust treatment standards EURO 4 and EURO 5.

07/11-49260-15 Page 2 of 2

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



ZG Division  
Divinol  
Lubricants + Release Agents

Zeller + Gmelin GmbH & Co. KG  
Schlossstraße 20 · D 73054 Eisligen/Fils  
Phone +49 7161 802-0 Fax +49 7161 802-330

[www.zeller-gmelin.de](http://www.zeller-gmelin.de) [info@zeller-gmelin.de](mailto:info@zeller-gmelin.de)

