



TECHNICAL DATA SHEET

Divinol Asphalt Aqua PK

Label-free asphalt release agent concentrate based on plants raw materials

PRODUCT DESCRIPTION

- + water-miscible concentrate
- + on the basis of renewable raw materials
- + label-free
- + Mineral oil and VOC-free (solvent-free)
- + economical in use

CHARACTERISTICS

Colour / Appearance	yellowish, clear
---------------------	------------------

Density/15°C / DIN EN ISO 12185	920 kg/m ³
---------------------------------	-----------------------

Viscosity/20°C / ASTM D 7042	80 mm ² /s
------------------------------	-----------------------

Flash point (Cleveland) / DIN ISO 2592	> 250 °C
--	----------

Pour point / ASTM D 7346	< -9 °C
--------------------------	---------

pH-value (10 % in distilled H ₂ O) / DIN 51 369	6.8
--	-----

Water hazardous class	1
-----------------------	---

APPLICATION

09480

06/2023-09480-29

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Asphalt Aqua PK

Label-free asphalt release agent concentrate based on plants raw materials

Divinol Asphalt Aqua PK is a water-miscible concentrate for the production of a release agent for rolled asphalt.

It is ideally suited for all types of asphalt rollers (rubber + combi).

The application occurs with a suitable spray device or with a brush.

Divinol Asphalt Aqua PK has proven excellent as a welding release agent. It effectively prevents the adhesion of welding spatters. The emulsion is sprayed thinly onto the steel workpiece to be welded - or applied with a cloth, after which the welding process takes place. Finally, any welding spatters or stains that may still adhere slightly are wiped off easily.

WORKING CONCENTRATION

for roller-compacted asphalt: approx. 10 - 20 %

as release agent for welding spatters: approx. 20 - 25 %

PREPARATION OF THE EMULSION

To receive an emulsion first add water, then add concentrate by stirring continuously

NOTE / ATTENTION

Only mix quantities which can be consumed within one working day.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

09480

06/2023-09480-29

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.