

TECHNICAL DATA SHEET

Divinol HLP ISO 68 FF

High pressure hydraulic oil, mineral based according to the requirements of DIN 51 524 part 2, HLP - viscosity: 68 mm²/s/40°C

PRODUCT DESCRIPTION

- + ultra-fine filtered high pressure hydraulic oil according to DIN ISO 4406
- + on the basis of mineral oil
- + with oxidation and corrosion inhibitors
- + with friction and wear inhibitors
- + fulfils the requirements for hydraulic oils according to DIN 51 524 part 2, HLP
- + Purity class 14/11

CHARACTERISTICS

Colour / DIN ISO 2049	lighter 2.5
Density/15°C / DIN EN ISO 12185	890 kg/m³
Viscosity/40°C / ASTM D 7042	68 mm²/s
Viscosity index / ASTM D 2270	95
Flash point (Cleveland) / DIN ISO 2592	> 200 °C
Pour point / DIN ISO 3016	< -12 °C

APPLICATION

Divinol HLP ISO 68 FF can be used for all hydraulic aggregates, for which the usage of fine filtered HLP alloyed oils is prescribed.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

23320 02/2019-23320-6

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



TECHNICAL DATA SHEET

Divinol HLP ISO 68 FF

High pressure hydraulic oil, mineral based according to the requirements of DIN 51 524 part 2, HLP - viscosity: 68 mm²/s/40°C

23320 02/2019-23320-6

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2/2