



TECHNICAL DATA SHEET

Divinol Asphalt Pur MF

Ready to use asphalt separating agent for a wide area of application

PRODUCT DESCRIPTION

- + asphalt release agent ready to use
- + based on mineral oil
- + VOC-free (solvent-free)
- + suitable for temperatures up to 170 °C

CHARACTERISTICS

Colour / Appearance yellowish, clear

Density/15°C / DIN EN ISO 12185 890 kg/m³

Viscosity/20°C / ASTM D 7042 20 mm²/s

Flash point (Cleveland) / DIN ISO 2592 130 °C

Pour point / ASTM D 7346 < -40 °C

Water hazardous class 1

APPLICATION

Divinol Asphalt Pur MF is a ready to use asphalt and bitumen release agent for roller-compacted asphalt, stone mastic asphalt (SMA) and open-pore asphalt (OPA). It has an excellent release effect and can be used for asphalt mixing plants, asphalt recycling plants, road finishing machines, rubber-tire rollers, combi rollers and truck beds.

Application is by spraying or brushing.

31970

06/2023-31970-8

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Asphalt Pur MF

Ready to use asphalt separating agent for a wide area of application

PREPARATION OF THE EMULSION

Divinol Asphalt Pur MF is used pure

NOTE / ATTENTION

Don't get **Divinol Asphalt Pur MF** in touch with zinc or galvanized materials.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

31970

06/2023-31970-8

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

2 / 2