



## TECHNICAL DATA SHEET

# Divinol Asphalt Premium PK

Label-free asphalt release agent concentrate based on plants raw materials

## PRODUCT DESCRIPTION

- + water-miscible concentrate
- + on the basis of renewable raw materials
- + label-free
- + mineral oil and VOC free (solvent free)
- + economical in use
- + stable emulsion

## CHARACTERISTICS

Colour / Appearance	yellowish, clear
---------------------	------------------

Density/15°C / DIN EN ISO 12185	940 kg/m <sup>3</sup>
---------------------------------	-----------------------

Viscosity/20°C / ASTM D 7042	110 mm <sup>2</sup> /s
------------------------------	------------------------

Flash point (Cleveland) / DIN ISO 2592	> 250 °C
--	----------

Pour point / ASTM D 7346	< -9 °C
--------------------------	---------

pH-value (10 % in distilled H <sub>2</sub> O) / DIN 51 369	7.0
--	-----

Water hazardous class	1
-----------------------	---

## APPLICATION

32400

06/2023-32400-10

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



## TECHNICAL DATA SHEET

### Divinol Asphalt Premium PK

Label-free asphalt release agent concentrate based on plants raw materials

**Divinol Asphalt Premium PK** is a water-miscible concentrate for the production of a release agent for rolled asphalt. The prepared emulsion is at least 10 days shelf stable in a concentration of 20%.

Best suited for all types of street rollers (rubber rollers, combi rollers, etc.)

The application is applied by a suitable sprayer with by a brush.

#### WORKING CONCENTRATION

for roller-compacted asphalt: 20%

#### PREPARATION OF THE EMULSION

First add water, then add concentrate by stirring continuously.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

32400

06/2023-32400-10

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.