



## TECHNICAL DATA SHEET

# Divinol Getriebe- Hydrauliköl TO-4 10W

## Gear & Hydraulic Fluid TO-4 SAE 10W

### PRODUCT DESCRIPTION

Gear- and power-transmission oil in construction, commercial and logistics vehicles for power shift transmission, final drives, hydrostatic drives, torque converters, wet clutches and brakes as well as hydraulics, where special oils are necessary.

#### Advantages:

- + Optimal friction characteristics, also at low temperatures High anti wear protection even under heavy conditions
- + Professional protection for transmission gears under impact load
- + perfect corrosion protection
- + very good power transmission oil

### CHARACTERISTICS

Appearance	clear
Density/15°C / DIN EN ISO 12185	0,87 g/cm <sup>3</sup>
Viscosity/40°C / ASTM D 7042	41.5 mm <sup>2</sup> /s
Viscosity/100°C / ASTM D 7042	6.6 mm <sup>2</sup> /s
Flash point (Cleveland) / DIN ISO 2592	≥ 210 °C
Pour point / ASTM D 7346	-33 °C

### SPECIFICATION

API GL-4

48970

04/2024-48970-12

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

TECHNICAL DATA SHEET

## **Divinol Getriebe- Hydrauliköl TO-4 10W**

**Gear & Hydraulic Fluid TO-4 SAE 10W**

### **DIVINOL RECOMMENDATION**

Caterpillar TO-4; Caterpillar TO-2; Allison C-4; Dana; Eaton; Sperry Vickers M2905S & I-280S ; Komatsu Micro Clutch; Komatsu KES 07.868.1; JCB-Standard 4000/2500; ZF TE-ML 03C

### **APPLICATION**

Gear and transmission oil for manual gearboxes in construction machinery, final drives, hydrostatic transmissions, torque converters, clutches and wet brakes and hydraulic systems, in which special oils must be used.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

48970

04/2024-48970-12

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

2 / 2