

TECHNICAL DATA SHEET

Divinol Multilight FO 2 5W-30

Suitable for Ford and other engines

PRODUCT DESCRIPTION

Divinol Multilight FO 2 5W-30 is a special semi-synthetic oil for modern Ford diesel and otto motors. Especially during start and warm-up phase this quality motor oils guarantees fast oiling of the motor. The Ford specification WSS M2C 913D assures fuel saving properties.

CHARACTERISTICS

SAE Grade	5W-30
Appearance	L 3.0
Density/15°C / DIN EN ISO 12185	0,85 g/cm³
Viscosity/40°C / ASTM D 7042	58 mm²/s
Viscosity/100°C / ASTM D 7042	10.2 mm²/s
Viscosity index / ASTM D 2270	167
Flash point (Cleveland) / DIN ISO 2592	235°C
Pour point / ASTM D 7346	-45°C
TBN	8.5 mgKOH/g

49170

12/2023-49170-19

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Multilight FO 2 5W-30

Suitable for Ford and other engines

SPECIFICATION

ACEA A5/B5

MANUFACTURER APPROVAL

Ford WSS-M2C-913 D

DIVINOL RECOMMENDATION

Ford WSS-M2C-913-A; Ford WSS-M2C-913-B; Ford WSS-M2C-913-C; Ford WSS-M2C-925-A; Renault RN 0700; STJLR.03.5003

APPLICATION

Divinol Multilight FO 2 5W-30 is suitable for otto and diesel motors according to OEMs regulations. In particular suitable for Ford vehicles.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

EXPERTLY DONE.

12/2023-49170-19

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

Zeller+Gmelin GmbH & Co. KG · Schlossstraße 20 · 73054 Eislingen/Fils · Germany · Postfach 13 65 · 73054 Eislingen/Fils Phone: +49 7161 802-0 · Fax: +49 7161 802-290 · info@zeller-gmelin.de · Geschäftsführer: Dipl.-Ing. (FH) Siegfried Müller Dipl.-Kfm.WalterJerusalem·Dipl.-Ing.(FH)ThomasAlpers·KommanditgesellschaftSitzEislingen·AmtsgerichtUlmHRA530107 Persönlich haftende Gesellschafterin Zeller+Gmelin Verwaltungs GmbH · Sitz Eislingen · Amtsgericht Ulm HRB 530641