



TECHNICAL DATA SHEET

Divinol Bike Racer 4T 5W-40

High quality motor bike oil corresponding JASO MA2 / wet clutch transmission

PRODUCT DESCRIPTION

Divinol Bike Racer 4T 5W-40 is a modern, multipurpose engine oil especially for motorbikes or quads based on the most modern HC synthesis technology with up to date JASO MA2. Divinol Bike Racer 4T 5W-40 specially supports wet clutch transmissions in motorbikes and reduces sludge in the motor. High alkaline reserves guarantee good corrosion protection. The new formulation saves fuel and reduces oil consumption. A multipurpose oil for every season.

CHARACTERISTICS

Colour / DIN ISO 2049	4.0
SAE Grade	5W40
Density/15°C / DIN EN ISO 12185	0,860 g/cm ³
Ash / Sulfate DIN 51575	0.9 %
Viscosity/40°C / ASTM D 7042	87 mm ² /s
Viscosity/100°C / ASTM D 7042	14.3 mm ² /s
Viscosity index / ASTM D 2270	172
Flash point (Cleveland) / DIN ISO 2592	>= 195 °C

49521

02/2024-49521-8

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Bike Racer 4T 5W-40

High quality motor bike oil corresponding JASO MA2 / wet clutch transmission

Pour point / ASTM D 7346	-39 °C
--------------------------	--------

TBN	10.8 mgKOH/g
-----	--------------

SPECIFICATION

API SP/CF; JASO MA2

APPLICATION

Multi-purpose motor oil for two-wheeled vehicles or quads.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49521

02/2024-49521-8

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.