



TECHNICAL DATA SHEET

Divinol Multilight 10W-40

Premium Multigrade oil SAE 10W-40

PRODUCT DESCRIPTION

Modern low-friction engine oil for gasoline and diesel engines in cars, formulated based on high-quality base oils. This engine oil is suitable for use in modern car engines with and without turbochargers, even under difficult operating conditions. By using selected additives, special raffinates and base oil from HC synthesis technology, deposits are reduced and sludge is prevented. High alkaline reserves ensure good corrosion protection properties. A modern formulation concept results in fuel savings and a reduction in oil consumption. Also suitable for motorcycles according to the JASO MA standard. Please stick to manufacturer's instructions!

CHARACTERISTICS

Colour / DIN ISO 2049	3.5
SAE Grade	10W-40
Density/15°C / DIN EN ISO 12185	0,86 g/cm ³
Ash / Sulfate DIN 51575	1.2 %
Viscosity/40°C / ASTM D 7042	90 mm ² /s
Viscosity/100°C / ASTM D 7042	13.5 mm ² /s
Viscosity index / ASTM D 2270	160
Flash point (Cleveland) / DIN ISO 2592	230 °C
Pour point / ASTM D 7346	-36 °C

49610

03/2024-49610-37

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Multilight 10W-40

Premium Multigrade oil SAE 10W-40

TBN 10 mgKOH/g

SPECIFICATION

API SN/CF; ACEA A3/B4; JASO MA

MANUFACTURER APPROVAL

Meet MB 229.1H specification

DIVINOL RECOMMENDATION

MB 229.3; VW 505.00/501.01; PSA B71 2294; Renault RN 0700; FIAT 9.55535-G2

APPLICATION

Multi-purpose motor oil for all Otto and Diesel engines with or without turbo charger.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49610

03/2024-49610-37

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.