



## TECHNICAL DATA SHEET

### Divinol ATF Pro 9G LV

Low-viscosity, red premium ATF for Ultra Low Viscosity Application & MB 236.17

#### PRODUCT DESCRIPTION

Divinol ATF Pro 9G LV is a fuel-saving automatic transmission oil with reduced viscosity (LV = Low Viscosity application). Sophisticated additive components in combination with high quality base oils allow to formulate thinner automatic oils which meet the requirements of modern transmission technology and combine ecology / economic thoughts.

The excellent temperature characteristics allow a broad use and ensure optimal operating conditions under high and low temperatures. Good shifting characteristics, a very good aging / oxidation stability and long oil drain intervals are also provided by the use of high quality synthesis-technology base oils .

#### Advantages:

- + excellent oxidation stability
- + excellent wear protection
- + excellent cold flow characteristics
- + wide temperature range
- + good seal compatibility
- + excellent shear stability
- + for extended oil change intervals
- + ATF for LV - applications
- + can be used in **hybrid vehicles**

#### CHARACTERISTICS

Appearance	red
Density/15°C / DIN EN ISO 12185	0,839 kg/m <sup>3</sup>

51710

12/2022-51710-2

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



## TECHNICAL DATA SHEET

### Divinol ATF Pro 9G LV

Low-viscosity, red premium ATF for Ultra Low Viscosity Application & MB 236.17

---

Viscosity/40°C / ASTM D 7042	26.5 mm <sup>2</sup> /s
------------------------------	-------------------------

---

Viscosity/100°C / ASTM D 7042	5.5 mm <sup>2</sup> /s
-------------------------------	------------------------

---

Viscosity index / ASTM D 2270	150
-------------------------------	-----

---

Flash point (Cleveland) / DIN ISO 2592	≥ 180 °C
--	----------

---

Pour point / ASTM D 7346	≤ -45 °C
--------------------------	----------

---

#### SPECIFICATION

JASO 1-A-LV; Dexron ULV; Mercon ULV

#### DIVINOL RECOMMENDATION

MB 236.16; MB 236.17; ZF 9 Speed (AA01.500.001); Ford WSS M2C 949-A

#### APPLICATION

Divinol ATF Pro 9G LV is suitable as transmission oil in automatic transmissions of cars, LCV's and special vehicles.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

51710

12/2022-51710-2

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.