



TECHNICAL DATA SHEET

Divinol ATF Premium VI LV

Low-viscosity, red premium ATF oil Dexron VI

PRODUCT DESCRIPTION

Divinol ATF Premium VI LV is a fuel-saving automatic transmission oil with reduced viscosity (LV = Low Viscosity application). Sophisticated additive components in combination with high quality base oils allow to formulate thinner automatic oils which meet the requirements of modern transmission technology and combine ecology / economic thoughts.

The excellent temperature characteristics allow a broad use and ensure optimal operating conditions under high and low temperatures. Good shifting characteristics, a very good aging / oxidation stability and long oil drain intervals are also provided by the use of high quality synthesis-technology base oils .

Advantages:

- + excellent oxidation stability
- + excellent wear protection
- + excellent cold flow characteristics
- + wide temperature range
- + good seal compatibility
- + excellent shear stability
- + for extended oil change intervals
- + ATF for LV - applications
- + can be used in **hybrid vehicles**

CHARACTERISTICS

| | |
|------------|-----|
| Appearance | red |
|------------|-----|

| | |
|---------------------------------|------------------------|
| Density/15°C / DIN EN ISO 12185 | 0,85 g/cm ³ |
|---------------------------------|------------------------|

51760

07/2023-51760-27

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol ATF Premium VI LV

Low-viscosity, red premium ATF oil Dexron VI

| | |
|------------------------------|-----------------------|
| Viscosity/40°C / ASTM D 7042 | 29 mm ² /s |
|------------------------------|-----------------------|

| | |
|-------------------------------|----------------------|
| Viscosity/100°C / ASTM D 7042 | 6 mm ² /s |
|-------------------------------|----------------------|

| | |
|-------------------------------|-----|
| Viscosity index / ASTM D 2270 | 155 |
|-------------------------------|-----|

| | |
|--|--------|
| Flash point (Cleveland) / DIN ISO 2592 | 210 °C |
|--|--------|

| | |
|--------------------------|--------|
| Pour point / ASTM D 7346 | -45 °C |
|--------------------------|--------|

SPECIFICATION

Dexron VI; Dexron HP; Mercon LV; JASO 1-A; JASO 1-A-LV

DIVINOL RECOMMENDATION

MB 236.12/.14/.15./41; VW G 052 162; VW G 055 005; VW G 055 162; VW G 055 540; VW G 060 162; BMW 83 22 0 142 516; BMW 83 2 22 152 426; BMW 83 22 2 355 599; BMW 83 22 2 289 720; BMW M-1375.4; Toyota WS; Nissan Matic-S; Nissan Matic-W; Mitsubishi SP-IV; Mitsubishi Dia Queen ATF-PA; Mitsubishi ATF-J3; Fiat 9.55550-AV5; Hyundai/KIA SP-IV; Hyundai/KIA SPH-IV; Hyundai FF-SP-IV M; Hyundai NWS-9638; Honda DW-1; Honda 3.1; JWS 3324; Aisin Warner GM-AW-1; Saab 93 165 147 AW1; Bentley JNV 862 564; Mazda ATF FZ; Mazda ATF 3.1; Jaguar 02JDE26444; Land Rover LR023288; Hyundai/ KIA SP-IV RR; ZF 6 Speed (S671 090 255); ZF 8 Speed (S671 090 312); Volvo P/N 31256774 ; Volvo 31246675

APPLICATION

Divinol ATF Premium VI LV is suitable as transmission oil in automatic transmissions of cars, LCV's and special vehicles.

51760

07/2023-51760-27

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol ATF Premium VI LV

Low-viscosity, red premium ATF oil Dexron VI

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

51760

07/2023-51760-27

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.