



TECHNICAL DATA SHEET

Divinol ATF-C Premium VI

Clear premium ATF gear oil Dexron VI

PRODUCT DESCRIPTION

Divinol ATF-C Premium VI is a clear colored power transmission oil for automatic transmissions and offers following characteristics:

- + Superior oxidation stability
- + Very good anti wear characteristics
- + Premium cold flow properties
- + Broadly temperature range deployment
- + Not aggressive to any sort of seal
- + Very good shear stability
- + Suitable for prolonged oil drain intervals
- + Universal deployable ATF
- + can be used in **hybrid vehicles**

CHARACTERISTICS

Colour / DIN ISO 2049	L 2.0
Appearance	brown, clear
Density/15°C / DIN EN ISO 12185	0,85 g/cm ³
Viscosity/40°C / ASTM D 7042	34 mm ² /s
Viscosity/100°C / ASTM D 7042	6.7 mm ² /s

51800

01/2024-51800-35

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol ATF-C Premium VI

Clear premium ATF gear oil Dexron VI

Viscosity index / ASTM D 2270	156
Flash point (Cleveland) / DIN ISO 2592	222 °C
Pour point / ASTM D 7346	- 48 °C

SPECIFICATION

GM Dexron VI*; GM Dexron III G/H; GM Dexron II D; GM Dexron TASA; Ford Mercon V; JASO 1 A

DIVINOL RECOMMENDATION

MB 236.3/ 236.5 / 236.6 /236.7 / 236.8 / 236.9 / 236.91/ 236.10 / 236.11; DTFR 13C170; DTFR 13C180 (236.91); VW G 052 025 / G 052 162 / G 052 990 / G 055 025 / G US 000 162; BMW / MINI P/N 81 22 9 400 272/275, BMW / MINI P/N 81 22 9 407 858/859; BMW / MINI P/N 83 22 0 024 249/359, BMW / MINI P/N 83 22 0 026 922, BMW / MINI P/N 83 22 0 402 413, BMW / MINI P/N 83 22 0 403 248, BMW / MINI P/N 83 22 0 403 249, BMW / MINI P/N 83 22 7 542 290, BMW / MINI P/N 83 22 9 407 765, BMW / MINI P/N 83 22 9 407 807, Porsche P/N 000 043 204 41, Porsche P/N 000 043 205 09, Porsche P/N 000 043 205 28, Porsche P/N 999 917 547 00, PSA Peugeot Citroën P/N Z 000169756, Renault Matic D2, Hyundai/Kia SP II / III, Mazda ATF M V, Mazda ATF M III, Mazda Type T-IV, Mazda ATF F1, Mitsubishi ATF-J2, Mitsubishi SP (P/N MS991156), Mitsubishi SP-II, Mitsubishi SP-III, Nissan / Infinity N402, Matic D/J/K, Subaru ATF HP, Subaru P /N K0140Y0700, Volvo P/N 1161521, Volvo P/N 1161540/1161640, Volvo VCE 1273.41, Volvo 97341; Volvo 6 Speed (P/N 31256774 & 31246675), Chrysler ATF +/2/3/4, Honda ATF- Z1, Hyundai/Kia SP-II / III, Suzuki 3314, Suzuki 3317, JWS 3309; Saab 3309 - T-IV, Isuzu ATF III, Isuzu P/N 08200-9001, Bentley JNV 862 564 D, SangYong DSIH 5M-66, Jaguar JLM 20238, Jaguar JLM 21044, Jaguar K17, Jaguar WSS-M2C922-A1, Idemitsu K17 / ATF HP, ZF TE ML- 05L,09,11A,11B,21L, ZF 6 Speed (S671 090 255), Allison C4 / TES 295 / TES 389, Voith 55.6335.XX (G607), MAN 339A/D/F/L1

*Viscosity requirements not met

APPLICATION

51800

01/2024-51800-35

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol ATF-C Premium VI

Clear premium ATF gear oil Dexron VI

Divinol ATF-C Premium VI is suitable as transmission oil in automatic transmissions of cars, trucks, busses and special vehicles. Also possible for hydrodynamic converters, hydraulics and servo-steerings in accordance to manufacturers' specifications.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

51800

01/2024-51800-35

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.