



TECHNICAL DATA SHEET

Divinol ATF Spezial R

Red ATF gear oil Dexron III G

PRODUCT DESCRIPTION

Divinol ATF Spezial R is a power transmission oil for automatic transmissions and fulfils the following requirements:

- + Superior oxidation stability
- + Very good anti wear characteristics
- + Premium cold flow properties
- + Broad temperature range deployment
- + Not aggressive to any sort of seal

CHARACTERISTICS

Appearance	red
Density/15°C / DIN EN ISO 12185	870 kg/m ³
Viscosity/40°C / ASTM D 7042	35 mm ² /s
Viscosity/100°C / ASTM D 7042	7.1 mm ² /s
Viscosity index / ASTM D 2270	170
Flash point (Cleveland) / DIN ISO 2592	200 °C
Pour point / ASTM D 7346	<=-40 °C

SPECIFICATION

51830

01/2024-51830-22

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol ATF Spezial R

Red ATF gear oil Dexron III G

GM Dexron III G; GM Dexron II D; GM Dexron TASA; Ford Mercon 2004

MANUFACTURER APPROVAL

DTFR 13C170; Voith H55.6335.XX; ZF TE-ML 03D/04D/14A/17C (ZF009444)

DIVINOL RECOMMENDATION

Allison C-4; MAN 339 V1/Z1/L1; MB 236.9; Volvo 97340 / 97341; JCB Standard 4000/2300; ZF-TE-ML 09/21L

APPLICATION

Divinol ATF Spezial R is suitable as transmission oil in automatic transmissions of cars, trucks, busses and special vehicles. Also possible for hydrodynamic converters, hydraulics and servo-steerings in accordance to manufacturers` specifications.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

51830

01/2024-51830-22

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.