



TECHNICAL DATA SHEET

Divinol CVT Fluid

CVT-Gearboxes

PRODUCT DESCRIPTION

Divinol CVT Fluid is a high performance automatic transmission oil based on the latest synthetic oil technology. This product is developed specifically for use in CVT transmissions with push belt or traction chain of steel. It offers optimal protection against foaming, as it has a very good aging and oxidation stability. Divinol CVT Fluid is specially suitable for Autotronic in Mercedes Benz A-and B-class as well as for Multitronic in Audi vehicles. Divinol CVT Fluid can be used in **hybrid vehicles**.

CHARACTERISTICS

Appearance	Red
Density/15°C / DIN EN ISO 12185	0,85 g/cm ³
Viscosity/40°C / ASTM D 7042	33 mm ² /s
Viscosity/100°C / ASTM D 7042	7 mm ² /s
Viscosity index / ASTM D 2270	180
Flash point (Cleveland) / DIN ISO 2592	210 °C
Pour point / ASTM D 7346	< -48 °C

51870

07/2023-51870-17

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol CVT Fluid

CVT-Gearboxes

DIVINOL RECOMMENDATION

MB 236.20; Nissan NS-1, NS-2, NS-3; BMW Mini Cooper EZL799; Punch CVT; Daihatsu Ammix CVT DFE; Shell Green 1V; Daihatsu Ammix CVT Fluid DC; Subaru iCVT; Daihatsu Ammix CVT Fluid DFC; Subaru iCVT FG; Dodge / Jeep / Chrysler NS-2; Subaru ECVT; Dodge / Chrysler / Jeep Mopar CVT+4; Subaru Lineartronic chain CVT and CVT II Fluid; GM / Saturn DEX-CVT; Subaru Lineartronic High Torque (HT) CVT Fluid; Honda HMMF (no starting clutch); Suzuki CVTF TC; Honda HCF2; Suzuki CVTF 3320; Honda Z-1 (CVT, no starting clutch); Suzuki NS-2 (not SFU for 2001 – 2007 Honda Fit & Jazz); Suzuki CVT Green 1&2; Hyundai / KIA SP III (CVT); Toyota CVTF TC; Idemitsu CVTS-EX1; Toyota CVTF FE; Mazda JWS 3320; VW TL 521 16 (G 052 516); VW TL 521 80 (G 052 180); Audi Multitronic; Mitsubishi Diaqueen CVTF-J1; Mitsubishi Diaqueen CVTF-J4 and J4+; Mitsubishi Diaqueen SP-III (CVT model only)

APPLICATION

Divinol CVT Fluid can be deployed as transmission oil in automatic CVT (*Continuously Variable Transmission*) gears of passenger cars.

Please see manufacturer's instructions.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

51870

07/2023-51870-17

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.