

TECHNICAL DATA SHEET

Divinol Bremsflüssigkeit DOT 4

Brake Fluid DOT 4

PRODUCT DESCRIPTION

High-quality synthetic brake fluid especially made for use in brake systems with drum and/or disk brakes for which a brake fluid according to DOT 4 is required. Ideal for all hydraulic car-brake and clutch systems except for systems designed for operation with mineral oil.

- + good ageing stability
- + does not affect sealing material
- + minimum corrosion
- + high wet boiling point

CHARACTERISTICS

Colour / DIN ISO 2049 < 3.5

Density/15°C / DIN EN ISO 12185 1,065 kg/m³

SPECIFICATION

FMVSS 116 DOT 4; SAE J 1704; ISO 4925

Wet boiling point >155 °C FMVSS 116

Boiling point (reflux) >250 °C FMVSS 116

Viscosity / -40°C 1200 mm²/s FMVSS 116

Viscosity / 100°C 2,3 mm²/s FMVSS 116

62170 08/2020-62170-4

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1/2



TECHNICAL DATA SHEET

Divinol Bremsflüssigkeit DOT 4

Brake Fluid DOT 4

APPLICATION

Use in all hydraulic brake systems with drum and/or disk brakes for which synthetic brake fluids according to DOT 4 are required. Miscible with all brake fluids complying with the same requirements.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

62170 08/2020-62170-4

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2/2