



## TECHNICAL DATA SHEET

# Divinol Kettenöl H

Mineral chain saw oil  $V_{40}= 100 \text{ mm}^2/\text{s}$

### PRODUCT DESCRIPTION

Chain oil with adhesive agent for high-performance motor saws. A very low wear of chains and rails can be guaranteed due to additives which are improving the lubrication.

### CHARACTERISTICS

Colour / DIN ISO 2049	D 8.0
Appearance	dark brown - black, clear
Density/15°C / DIN EN ISO 12185	0,890 g/cm <sup>3</sup>
Viscosity/40°C / ASTM D 7042	100 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270	110
Flash point (Cleveland) / DIN ISO 2592	200 °C
Pour point / ASTM D 7346	-21 °C
Loading capacity according to Brugger / DIN 51 347	$\geq 36 \text{ N/mm}^2$

### APPLICATION

Divinol Kettenöl H offers adhesive strength and due to wear preventive additives best lubrication for chain saws. Optimal lubrication even under hard conditions with high performance reserves. For cleaning Divinol recommends our DIVINOL Gerätereiniger Forte.

84150

08/2020-84150-15

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

TECHNICAL DATA SHEET

## Divinol Kettenöl H

Mineral chain saw oil  $V_{40}= 100 \text{ mm}^2/\text{s}$

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

84150

08/2020-84150-15

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2

**EXPERTLY DONE.**

Zeller+Gmelin GmbH & Co. KG · Schlossstraße 20 · 73054 Eisligen/Fils · Germany · Postfach 13 65 · 73054 Eisligen/Fils  
Phone: +49 7161 802-0 · Fax: +49 7161 802-290 · info@zeller-gmelin.de · Geschäftsführer: Dipl.-Ing. (FH) Siegfried Müller  
Dipl.-Kfm. Walter Jerusalem · Dipl.-Ing. (FH) Thomas Alpers · Kommanditgesellschaft · Sitz Eisligen · Amtsgericht Ulm HRA 530107  
Persönlich haftende Gesellschafterin Zeller+Gmelin Verwaltungs GmbH · Sitz Eisligen · Amtsgericht Ulm HRB 530641