



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL MULTISPRAY M 2000 MIT MoS₂

Material number 12100

Revision date: 15.12.2023

Version: 5.0

Replaces version: 4.3

Language: en-DE

Date of print: 19.12.2023

Page: 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: AUTOL MULTISPRAY M 2000 MIT MoS₂

UFI: ERA0-F036-X00R-H8YY

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Lubricant

1.3 Details of the supplier of the safety data sheet

Company name: Eni Schmiertechnik GmbH

Street/POB-No.: Paradiesstraße 14

Postal Code, city: 97080 Würzburg

Germany

WWW: www.enischmiertechnik.de

E-mail: info.wuerzburg@eni.com

Telephone: +49 (0)931-90098-0

Telefax: +49 (0)931-98442

Department responsible for information:

Application Engineering & Product Management (AEPM)

Telephone: +49 (0)931-90098-0

E-mail: technik.wuerzburg@eni.com

1.4 Emergency telephone number

GIZ-Nord, Göttingen

Telephone: +49 (0)551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Aerosol 1; H222; H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

STOT SE 3; H336 May cause drowsiness or dizziness.

Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

(EUH066) Repeated exposure may cause skin dryness or cracking.

2.2 Label elements

Labelling (CLP)



Signal word:

Danger

Hazard statements:

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H336

May cause drowsiness or dizziness.

EUH066

Repeated exposure may cause skin dryness or cracking.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL MULTISPRAY M 2000 MIT MoS₂

Material number 12100

Revision date: 15.12.2023

Version: 5.0

Replaces version: 4.3

Language: en-DE

Date of print: 19.12.2023

Page: 2 of 12

Precautionary statements:	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P260	Do not breathe vapours and spray.
	P312	Call a POISON CENTER/doctor if you feel unwell.
	P405	Store locked up.
	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	P501	Dispose of contents/container to hazardous or special waste collection point.

Special labelling

Text for labelling:

Contains:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided.

Inhaling can lead to irritations of the respiratory tract and mucous membrane.

Higher doses may lead to a narcotic effect.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Blend of active ingredients with propellant:



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL MULTISPRAY M 2000 MIT MoS2

Material number 12100

Revision date: 15.12.2023

Version: 5.0

Replaces version: 4.3

Language: en-DE

Date of print: 19.12.2023

Page: 3 of 12

Hazardous ingredients:

Identifiers	Designation Classification	Content
REACH 01-2119463258-33-xxxx list no. 919-857-5 CAS 64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3; H226. STOT SE 3; H336. Asp. Tox. 1; H304. (EUH066).	25 - 50 %
REACH 01-2119474878-16-xxxx EC No. 276-737-9 CAS 72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based Asp. Tox. 1; H304.	10 - 25 %
REACH 01-2119456620-43-xxxx list no. 926-141-6 CAS 64742-47-8	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics Asp. Tox. 1; H304. (EUH066).	2,5 - 10 %
REACH 01-2119474691-32-xxxx EC No. 203-448-7 CAS 106-97-8	Butane Flam. Gas 1A; H220. Press. Gas (Liq.); H280.	10 - 25 %
REACH 01-2119486944-21-xxxx EC No. 200-827-9 CAS 74-98-6	Propane Flam. Gas 1A; H220. Press. Gas (Liq.); H280.	10 - 25 %
REACH 01-2119485395-27-xxxx EC No. 200-857-2 CAS 75-28-5	Isobutane Flam. Gas 1A; H220. Press. Gas (Liq.); H280.	2,5 - 10 %

Full text of H- and EUH-statements: see section 16.

Additional information: The highly refined mineral oil contains <3% (w/w) DMSO extract, according to IP346.
Information about Butane and Isobutane:
Contains < 0,1 % 1,3-Butadiene.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: IF exposed or concerned: Get medical advice/attention. First aider: Pay attention to self-protection!

In case of inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if problems persist.

Following skin contact: Immediately clean with water and soap followed by thorough rinsing. In case of skin reactions, consult a physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After swallowing: Rinse mouth with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Caution if victim vomits: Risk of aspiration! Keep airway open. Immediately get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Aspiration hazard: in case of swallowing or vomiting danger of penetration into the lungs.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL MULTISPRAY M 2000 MIT MoS2

Material number 12100

Revision date: 15.12.2023

Version: 5.0

Replaces version: 4.3

Language: en-DE

Date of print: 19.12.2023

Page: 4 of 12

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Water spray jet, alcohol resistant foam, extinguishing powder and carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated.

May form dangerous gases and vapours in case of fire. Furthermore, there may develop:

Pyrolysis products, carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Heating will lead to pressure increase: Danger of bursting and explosion. Use fine water spray to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe vapours and spray. Avoid contact with the substance.

If possible, eliminate leakage. In case of leakage, eliminate all ignition sources. Provide adequate ventilation.

Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Keep unprotected people away.

Cordon off downwind area at risk and warn inhabitants.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion!

In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

6.4 Reference to other sections

Refer additionally to section 8 and 13.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL MULTISPRAY M 2000 MIT MoS₂

Material number 12100

Revision date: 15.12.2023

Version: 5.0

Replaces version: 4.3

Language: en-DE

Date of print: 19.12.2023

Page: 5 of 12

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe vapours and spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation. When handling large quantities, supply emergency spray. Have eye wash bottle or eye rinse ready at work place.

Precautions against fire and explosion: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers: Keep container tightly closed and in a well-ventilated place. Keep container dry. Keep only in the original container. Keep in a cool place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store containers in upright position. Storage temperature: 15 - 35 °C. Storage stability: ≥ 24 months.

Hints on joint storage: Do not store together with: Oxidizing agents. Keep away from food, drink and animal feedingstuffs.

Storage class: 2B = Aerosols

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
64742-47-8	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Germany: DFG Kurzzeit	20 mg/m ³ (Aerosol, respirable fraction)
		Germany: DFG Langzeit	5 mg/m ³ (Aerosol, respirable fraction)
		Germany: TRGS 900 Kurzzeit	600 mg/m ³ (hydrocarbons, aliphatic, C9-C14)
		Germany: TRGS 900 Langzeit	300 mg/m ³ (hydrocarbons, aliphatic, C9-C14)
106-97-8	Butane	Germany: TRGS 900 Kurzzeit	9600 mg/m ³ ; 4000 ppm
		Germany: TRGS 900 Langzeit	2400 mg/m ³ ; 1000 ppm
74-98-6	Propane	Germany: TRGS 900 Kurzzeit	7200 mg/m ³ ; 4000 ppm
		Germany: TRGS 900 Langzeit	1800 mg/m ³ ; 1000 ppm
75-28-5	Isobutane	Germany: TRGS 900 Kurzzeit	9600 mg/m ³ ; 4000 ppm
		Germany: TRGS 900 Langzeit	2400 mg/m ³ ; 1000 ppm



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL MULTISPRAY M 2000 MIT MoS₂

Material number 12100

Revision date: 15.12.2023

Version: 5.0

Replaces version: 4.3

Language: en-DE

Date of print: 19.12.2023

Page: 6 of 12

DNEL/DMEL: Information about Hydrocarbons, C₉-C₁₁, n-alkanes, isoalkanes, cyclics, <2% aromatics:
DNEL workers, inhalative, systemic, long-term: 871 mg/m³
DNEL workers, dermal, systemic, long-term: 77 mg/kg bw/d
DNEL consumers, inhalative, systemic, long-term: 185 mg/m³
DNEL consumers, dermal, systemic, long-term: 46 mg/kg bw/d
DNEL consumers, oral, systemic, long-term: 46 mg/kg bw/d
Information about Lubricating oils (petroleum), C₁₅-C₃₀, hydrotreated neutral oil-based:
DNEL workers, inhalative, systemic, long-term: 2,73 mg/m³
DNEL workers, inhalative, local, long-term: 5,58 mg/m³
DNEL workers, dermal, systemic, long-term: 0,97 mg/kg bw/d
DNEL consumers, oral, systemic, long-term: 0,74 mg/kg bw/d

8.2 Exposure controls

Provide good ventilation and/or an exhaust system in the work area.

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded.
The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.
Use filter apparatus type A/P2.

Hand protection: Protective gloves according to DIN EN 374.
Glove material: Nitrile rubber
Breakthrough time: > 480 min
Layer thickness: 0,4 mm
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to DIN EN ISO 16321-1:2022.

Body protection: Flame retardant, antistatic and chemical resistant protective clothing.

General protection and hygiene measures:
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapours and spray.
Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.
Do not get in eyes, on skin, or on clothing.
When using do not eat or drink. Contaminated work clothing should not be allowed out of the workplace.
Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse.
Have eye wash bottle or eye rinse ready at work place.
When handling large quantities, supply emergency spray.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	gaseous
Colour:	Form: Aerosol yellowish
Odour:	pleasant odour
Odour threshold:	No data available
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	-44,5 °C (Propane)
Flammability:	Extremely flammable aerosol.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL MULTISPRAY M 2000 MIT MoS₂

Material number 12100

Revision date: 15.12.2023

Version: 5.0

Replaces version: 4.3

Language: en-DE

Date of print: 19.12.2023

Page: 7 of 12

Upper/lower flammability or explosive limits:	LEL (Lower Explosion Limit): 0,60 Vol-% (Propane) UEL (Upper Explosive Limit): 10,90 Vol-% (Propane)
Flash point/flash point range:	-97 °C (Propane)
Auto-ignition temperature:	240 °C
Decomposition temperature:	No data available
pH:	Not applicable
Viscosity, kinematic:	No data available
Water solubility:	Slightly miscible
Partition coefficient: n-octanol/water:	No data available
Vapour pressure:	No data available
Density:	at 20 °C: approx. 0,682 g/cm ³
Vapour density:	No data available
Particle characteristics:	Not applicable

9.2 Other information

Explosive properties:	Vapours can form explosive mixtures with air.
Oxidizing characteristics:	No data available
Auto-ignition temperature:	Not self-igniting
Solvent content:	34,2 %
Evaporation rate:	No data available
Additional information:	Pressure (20 °C): 5-6 bar Vapours are heavier than air.

SECTION 10: Stability and reactivity

10.1 Reactivity

Extremely flammable aerosol.
Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Pressurised container: May burst if heated.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5 Incompatible materials

Oxidizing agents.

10.6 Hazardous decomposition products

	No hazardous decomposition products when regulations for storage and handling are observed.
Thermal decomposition:	No data available



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL MULTISPRAY M 2000 MIT MoS2

Material number 12100

Revision date: 15.12.2023

Version: 5.0

Replaces version: 4.3

Language: en-DE

Date of print: 19.12.2023

Page: 8 of 12

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Mild irritant.

Serious eye damage/irritation: Based on available data, the classification criteria are not met. Mild irritant.

Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.

Skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): STOT SE 3; H336 = May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard: Asp. Tox. 1; H304 = May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties: No data available

Other information: Information about Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

LD50, Rat, oral: > 5.000 mg/kg (OECD 401)

LD50, Rabbit, dermal: > 5.000 mg/kg (OECD 402)

LC50, Rat, inhalative: > 5.000 mg/m³/8h (OECD 403)

Information about Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

LD50, Rat, oral: > 5.000 mg/kg (OECD 401)

LD50, Rabbit, dermal: > 2.000 mg/kg

LC50, Rat, inhalative: > 5 mg/L/4h

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Information about Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Algae toxicity:

NOEL Pseudokirchneriella subcapitata (green algae): ≥ 100 mg/L/72h (OECD 201)

Water Hazard Class: 1 = slightly hazardous to water (Self-classification (mixture).)

12.2 Persistence and degradability

Further details: No data available

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:

No data available



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL MULTISPRAY M 2000 MIT MoS2

Material number 12100

Revision date: 15.12.2023

Version: 5.0

Replaces version: 4.3

Language: en-DE

Date of print: 19.12.2023

Page: 9 of 12

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 16 05 04* = Gases in pressure containers (including halons) containing hazardous substances/Aerosol
* = Evidence for disposal must be provided.

Recommendation: Do not pierce or burn, even after use.
Special waste. Dispose of waste according to applicable legislation.
Do not dispose of with household waste.

Package

Recommendation: Dispose of waste according to applicable legislation.
Empty carefully and completely, if possible. Handle empty containers with care. Incineration may cause explosion.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID, ADN, IMDG, IATA-DGR:
UN 1950

14.2 UN proper shipping name

ADR/RID, ADN, IMDG: UN 1950, AEROSOLS
IATA-DGR: UN 1950, AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

ADR/RID, ADN: Class 2, Code: 5F
IMDG: Class 2.1, Subrisk -
IATA-DGR: Class 2.1

14.4 Packing group

ADR/RID, ADN, IATA-DGR: not applicable
IMDG: -

14.5 Environmental hazards

Dangerous for the environment: Substance/mixture is not environmentally hazardous according to the criteria of the UN model regulations.

Marine pollutant - IMDG: no





SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL MULTISPRAY M 2000 MIT MoS2

Material number 12100

Revision date: 15.12.2023

Version: 5.0

Replaces version: 4.3

Language: en-DE

Date of print: 19.12.2023

Page: 10 of 12

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board: RID: Kemmler-number 23, UN number UN 1950
Hazard label: 2.1
Special Provisions: 190 327 344 625
Limited quantities: 1 L
EQ: E0
Package - Instructions: P207 LP200
Package - Special Provisions: PP87 RR6 L2
Special provisions for packing together: MP9
Tunnel restriction code: (D)
Remarks: ADR/RID: Transport as "limited quantity" according to chapter 3.4 ADR/RID (> 8.000 kg total gross mass): Tunnel restriction code (E)

Inland waterway craft (ADN)

Hazard label: 2.1
Special Provisions: 190 327 344 625
Limited quantities: 1 L
EQ: E0
Equipment necessary: PP - EX - A
ventilation: VE01,VE04

Sea transport (IMDG)

EmS: F-D, S-U
Special Provisions: 63 190 277 327 344 381 959
Limited quantities: 1000 mL
Excepted quantities: E0
Package - Instructions: P207, LP200
Package - Provisions: PP87, L2
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: SW1 SW22
Segregation: SG69
Properties and observations: -
Segregation group: none

Air transport (IATA)

Hazard label: Flamm. gas
Excepted Quantity Code: E0
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special Provisions: A145 A167 A802
Emergency Response Guide-Code (ERG): 10L

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Germany

Storage class: 2B = Aerosols



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL MULTISPRAY M 2000 MIT MoS2

Material number 12100

Revision date: 15.12.2023

Version: 5.0

Replaces version: 4.3

Language: en-DE

Date of print: 19.12.2023

Page: 11 of 12

Water Hazard Class: 1 = slightly hazardous to water (Self-classification (mixture).)

Incident regulation: Richtlinie 2012/18/EU (Seveso III):
Physikalische Gefahren: Ziffer 1.2.3.1 = Code P3a, Mengenschwelle 150 000kg / 500 000kg

Technical guidance air: 5.2.5

Information on working limitations:
Observe employment restrictions for young people.
Observe employment restrictions for expectant or nursing mothers.

Further regulations, limitations and legal requirements:
No data available

National regulations - EC member states

Volatile organic compounds (VOC):

74,24 % by weight

Further regulations, limitations and legal requirements:

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances
[Seveso-III-Directive] refer to Germany, 12. BImSchV

Use restriction according to REACH annex XVII, no.: 3, 40

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Wording of the H-phrases under paragraph 2 and 3:

H220 = Extremely flammable gas.

H222 = Extremely flammable aerosol.

H226 = Flammable liquid and vapour.

H229 = Pressurised container: May burst if heated.

H280 = Contains gas under pressure; may explode if heated.

H304 = May be fatal if swallowed and enters airways.

H336 = May cause drowsiness or dizziness.

EUH066 = Repeated exposure may cause skin dryness or cracking.

Reason of change:

Changes in section 1: Product identifier (UFI)

Changes in section 2: Labelling

Changes in section 3: Composition / Information on ingredients

Changes in section 15: Regulatory information

General revision

Date of first version:

25.4.2022

Department issuing data sheet: see section 1: Department responsible for information



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL MULTISPRAY M 2000 MIT MoS2

Material number 12100

Revision date: 15.12.2023

Version: 5.0

Replaces version: 4.3

Language: en-DE

Date of print: 19.12.2023

Page: 12 of 12

Abbreviations and acronyms:

- ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- Aerosol: Aerosol
- AS/NZS: Australian Standards/New Zealand Standards
- Asp. Tox.: Aspiration toxicity
- CAS: Chemical Abstracts Service
- CFR: Code of Federal Regulations
- CLP: Classification, Labelling and Packaging
- DMEL: Derived minimal effect level
- DNEL: Derived no-effect level
- EC: European Community
- EN: European Standard
- EQ: Excepted quantities
- EU: European Union
- Flam. Gas: Flammable gases
- Flam. Liq.: Flammable liquid
- IATA: International Air Transport Association
- IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
- IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
- IMDG Code: International Maritime Dangerous Goods Code
- LC50: Median lethal concentration
- LD50: Lethal dose 50%
- LEL: Lower Explosion Limit
- MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
- NOEL: No Observed Effect Level
- OECD: Organisation for Economic Co-operation and Development
- OEL: Occupational Exposure Limit Value
- OSHA: Occupational Safety and Health Administration
- PBT: Persistent, bioaccumulative and toxic
- PNEC: Predicted no-effect concentration
- Press. Gas: Gases under pressure
- REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
- RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
- STOT SE: Specific target organ toxicity - single exposure
- TLV: Threshold Limit Value
- TRGS: Technical Rules for Hazardous Substances
- UN: United Nations
- vPvB: Very persistent and very bioaccumulative
- WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

Most recent product information is available at
<http://sumdat.net/a4zsv94b>

