

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878
Issue date: 12/09/2022 Revision date: 12/09/2022 Supersedes: 28/04/2022 Version: 6.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : Eni Rotra HY 80W-90

Product code : 1282
Type of product : Lubricants
Formula : 0038-2011
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use

Industrial/Professional use spec : Used in closed systems

Wide dispersive use

Use of the substance/mixture : Lubricant for gears

Do not use the product for any purposes that have not been advised by the manufacturer.

Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Eni S.p.A., P.le E. Mattei 1, 00144 Rom, ITALY, Tel. +39 06 59821, www.eni.com Competent person responsible for the safety data sheet (Reg. EC nr. 1907/2006): SDSInfo@eni.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY, www.oilproducts.eni.com Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0 e-mail: technik.wuerzburg@enilive.com

1.4. Emergency telephone number

Emergency number : CNIT +39 0382 24444 (24h) (IT + EN)

Poison centre (UK):

National Poisons Information Service Edinburgh (24h)

(+44) 844 892 0111 0870 600 6266 (UK only) (Source: UN-WHO)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects

Contact with eyes may cause temporary reddening and irritation. Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May produce an allergic reaction. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



CLP Signal word

Hazard statements (CLP)

: H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P273 - Avoid release to the environment.

P391 - Collect spillage.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

FUH-statements

: EUH208 - Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.. May produce an allergic reaction.

2.3. Other hazards (not relevant for classification)

Other hazards not contributing to the classification

: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. Do not wait for symptoms to develop. A potential risk may arise from the release of hydrogen sulfide, when the product is stored or handled at high temperature. Hydrogen sulfide may accumulate in the tanks or other confined spaces, with danger to the workers that enter the spaces. In these cases overexposure to hydrogen sulfide may cause irritation to airways, nausea, dizziness, loss of consciousness and death.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Component		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Mineral base oil, severely refined (light) (64741-89-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Component		
Distillates (petroleum), solvent-dewaxed heavy paraffinic(64742-65-0)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
C16-18-(even numbered, saturated and unsaturated)-alkylamines(1213789-63-9)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Notes

: Composition/Information on ingredients: Mixture of hydrocarbons Additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (EC Index-No.) 649-474-00-6 (REACH-no) 01-2119471299-27	70 – 80	Not classified
Residual oils (petroleum,) solvent-refined, Baseoil - unspecified (Component, see note [**], see note [***])	(CAS-No.) 64742-01-4 (EC-No.) 265-101-6 (EC Index-No.) 649-459-00-4 (REACH-no) 01-2119488707-21	15 - 20	Not classified
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (Additive)	(EC-No.) 931-384-6 (REACH-no) 01-2119493620-38	0,5 - 0,9	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

C16-18-(even numbered, saturated and unsaturated)-alkylamines (Additive)	(CAS-No.) 1213789-63-9 (EC-No.) 627-034-4 (REACH-no) 01-2119473797-19	0,2 - 0,4	Acute Tox. 4 (Oral), H302 (ATE=1689 mg/kg bodyweight) Skin Corr. 1B, H314 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
Distillates (petroleum), solvent-refined light paraffinic (For identification of the substance, see note [*], see note [***])	(CAS-No.) 64741-89-5 (EC-No.) 265-091-3 (EC Index-No.) 649-455-00-2 (REACH-no) 01-2119487067-30	0,04 - 0,4	Asp. Tox. 1, H304
Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs. (Additive) Substance included in REACH Candidate List (Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives)	(EC-No.) 939-460-0 (EC Index-No.) N/A (REACH-no) 01-2119971727-23	0,1 - 0,15	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (Additive)	(EC-No.) 931-384-6 (REACH-no) 01-2119493620-38	(9,39 <c 100)="" 1b,="" h317<br="" sens.="" skin="" ≤="">(50 <c 100)="" 2,="" eye="" h319<="" irrit.="" td="" ≤=""></c></c>

Notes

: [*] Note: this product may be formulated with one or more of the following severely refined mineral base oils (not classified as hazardous):

CAS 64742-54-7/EC 265-157-1/REACH Reg. # 01-2119484627-25-xxxx; CAS 64742-65-0/EC 265-169-7/REACH Reg. # 01-2119471299-27-xxxx; CAS 64742-70-7/EC 265-174-4/REACH Reg. # 01-2119487080-42-xxxx.

All these substances have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)

Note [**]:

this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

Note [***]:

substance with occupational exposure limits for some EU countries affecting the category of mineral oils (finely refined mineral base oil mists; see section 8.1)

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove to fresh air, keep the casualty warm and at rest. If breathing is difficult, give oxygen
	if possible, or assisted ventilation. If necessary, give external cardiac massage and obtain
	medical advice. See also section 4.3.

First-aid measures after skin contact

: Remove contaminated clothing and shoes. Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor.

First-aid measures after eye contact

: Remove contact lenses, if present and easy to do so. Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation persists, seek medical advice. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor.

12/09/2022 (Revision date) EN (English) 4/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

First-aid measures after ingestion

: Do not induce vomiting. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

: Inhalation of fumes or oil mists produced at high temperatures may cause irritation of the respiratory tract. Symptoms of overexposure to vapours include drowsiness, weakness, headache, dizziness, nausea, vomiting, dimming of vision.

Symptoms/effects after skin contact

: Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, due to a defatting effect. May cause an allergic skin reaction. Contact with hot product may cause thermal burns.

Symptoms/effects after eye contact

: Contact with eyes may cause temporary reddening and irritation. Contact with hot product or vapours may cause burns.

Symptoms/effects after ingestion

: Accidental ingestion of small quantities of the product may cause nausea, discomfort and gastric disturbances.

Symptoms/effects upon intravenous administration

: No information available.

Chronic symptoms

: None to be reported, according to the present classification criteria.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns. If there is any suspicion of inhalation of H2S (hydrogen sulphide). The casualty should be sent immediately to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

: Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations).

Unsuitable extinguishing media

: Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.

Explosion hazard

: In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m3 of air. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous decomposition products in case of fire

: Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, NOx, H2S and SOx (harmful/toxic gases). Oxygenated compounds (aldehydes, etc.). POx.

5.3. Advice for firefighters

Firefighting instructions

: Shut off source of product, if possible. If possible, move containers and drums away from danger area. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.

Special protective equipment for firefighters

: Personal protection equipment for firefighters (see also sect. 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN 443. EN 469. EN 659.

Other information

: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

12/09/2022 (Revision date) EN (English) 5/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid accidental sprays on hot surfaces or electrical contacts. Avoid direct contact with released material. Keep upwind.

6.1.1. For non-emergency personnel

Protective equipment Emergency procedures : See Section 8.

Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

6.1.2. For emergency responders

Protective equipment

Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (A) (or A+B when applicable for H2S), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

Emergency procedures

: Notify local authorities according to relevant regulations.

6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

6.3. Methods and material for containment and cleaning up

For containment

: Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.

Methods for cleaning up

: Transfer recovered product and other materials to suitable tanks or containers and store/dispose according to relevant regulations.

Other information

: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

12/09/2022 (Revision date) EN (English) 6/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. The product may release Hydrogen Sulphide: a specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".

Handling temperature Hygiene measures

- : This product can be handled at ambient temperatures.
- Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in dry, well ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.

Incompatible products

: Strong oxidizing agents.

Storage area

: Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills.

with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.

Packages and containers:

: If the product is supplied in containers: Keep containers tightly closed and properly labelled.

Keep only in the original container or in a suitable container for this kind of product.

Packaging materials

: For containers, or container linings use materials specifically approved for use with this

product. Compatibility should be checked with the manufacturer.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Residual oils (petroleum,) solvent-refined, Baseoil - unspecified (64742-01-4)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	MAK (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Residual oils (petroleum,) solvent-refined, Baseoil - unspecified (64742-01-4)		
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KTV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Distillates (petroleum), solvent-refined light pa	Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)		
Austria - Occupational Exposure Limits			
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Belgium - Occupational Exposure Limits	Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Denmark - Occupational Exposure Limits			
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Hungary - Occupational Exposure Limits			
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Netherlands - Occupational Exposure Limits			
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Sweden - Occupational Exposure Limits			
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
KTV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
United Kingdom - Occupational Exposure Limits			
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

This net on with a viscosity not less than 100 303 at 100 F (1303) at 40 C).] (04742-03-0)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KTV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

8.1.2. Recommended monitoring procedures

Monitoring methods	
Į ,	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Eni Rotra HY 80W-90	
DNEL/DMEL (additional information)	
Additional information Not applicable	
PNEC (additional information)	
Additional information Not applicable	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)		
DNEL/DMEL (Workers)		
160 μg/cm ²		
12,5 mg/kg bodyweight/day		
160 μg/cm²		
4,28 mg/m³		
160 μg/cm ²		
0,25 mg/kg bodyweight/day		
1,09 mg/m³		
6,25 mg/kg bodyweight/day		
160 μg/cm²		
2,4 µg/l		
0,24 μg/l		
150 μg/l		
15 μg/l		
12,9 μg/kg dw		
1,29 μg/kg dw		
1,17 μg/kg dw		
10 mg/kg food		
24,33 mg/l		

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	1 mg/m³
Long-term - systemic effects, dermal	0,09 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,38 mg/m³
Long-term - local effects, inhalation	1 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	40 μg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,035 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	0,26 μg/l
PNEC aqua (marine water)	0,026 μg/l
PNEC aqua (intermittent, freshwater)	1,6 µg/l

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

PNEC (Sediment)	
PNEC sediment (freshwater)	3,76 mg/kg dwt
PNEC sediment (marine water)	0,376 mg/kg dwt
PNEC (Soil)	
PNEC soil	10 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0,22 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	550 μg/l

Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	66,7 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,35 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0,33 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,58 mg/m³
Long-term - systemic effects, dermal	33,33 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	26 μg/l
PNEC aqua (marine water)	2,6 μg/l
PNEC aqua (intermittent, freshwater)	260 μg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1108,6 mg/kg dwt
PNEC sediment (marine water)	110,86 mg/kg dwt
PNEC (Soil)	
PNEC soil	221,48 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	6,7 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	45,5 mg/l

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

initiation on with a viscosity flot loss the	1 (1300t at 40 0). I (4742 00 0)	
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0,97 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2,73 mg/m³	
Long-term - local effects, inhalation	5,58 mg/m³	
DNEL/DMEL (General population) Long-term - systemic effects,oral 0,74 mg/kg bodyweight/day		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

PNEC (Oral)	
PNEC oral (secondary poisoning)	9,33 mg/kg food
PNEC (additional information) Additional information Not derived - Not classified as hazardous for environment	

Note

: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), check the atmosphere for oxygen content, presence of hydrogen sulphide (H2S) and SOx, and flammability. See also Section 16, "Other information".

8.2.2. Personal protection equipment

Personal protective equipment (for industrial or professional use):

Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask.

Personal protective equipment symbol(s):









8.2.2.1. Eye and face protection

Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure

8.2.2.2. Skin protection

Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

Hand protection:

Protective gloves. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

8.2.2.3. Respiratory protection

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: if the product is handled without adequate containment: use full or half-face masks with adequate filter for organic vapours. (EN 136/140/145). Combination filter device (DIN EN 141). Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H2S) or self-contained breathing apparatus (SCBA). (EN 136/140/145). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145)

8.2.2.4. Thermal hazards

Thermal hazard protection:

None in normal use conditions.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Do not discharge the product into the environment. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills.

Consumer exposure controls:

Wear protective gloves.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Yellow-brown.
Appearance : Liquid, bright & clear.
Odour : characteristic.
Odour threshold : Not determined

Melting point : -30 °C (pour point) (ASTM D 97)

Freezing point : Not determined
Boiling point : Not determined
Flammability : Not flammable

Explosive properties : None (according to composition).

Oxidising properties : None (according to composition).

Explosive limits : $\geq 45 \text{ g/m}^3 \text{ (Aerosol)}$ Lower explosive limit (LEL) : $\geq 45 \text{ g/m}^3 \text{ (Aerosol)}$ Upper explosive limit (UEL) : Not determined Flash point : 210 °C (ASTM D 92) Auto-ignition temperature : Not determined Decomposition temperature : Not determined pH : Not determined

Viscosity, kinematic : 130 mm²/s (40 °C) (ASTM D 445)
Solubility : Water: Immiscible and insoluble
Log Kow : Not applicable for mixtures
Log Pow : Not applicable for mixtures

Vapour pressure : 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)

Vapour pressure at 50 °C : Not determined

Density : 895 kg/m³ (15°C) (ASTM D 4052)

Relative density : Not determined Relative vapour density at 20 °C : Not determined Particle size : Not applicable Particle size distribution : Not applicable Particle shape : Not applicable : Not applicable Particle aspect ratio Particle aggregation state : Not applicable Particle agglomeration state : Not applicable : Not applicable Particle specific surface area Particle dustiness : Not applicable

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Additional information : No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

10.2. Chemical stability

Stable product, according to its intrinsic properties (in normal conditions of storage and handling).

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. Sensitivity to heat, friction or shock cannot be assessed in advance.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce: Carbon dioxide, Carbon monoxide. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. See also Section 16, "Other information".

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

Residual oils (petroleum,) solvent-refined, Baseoil - unspecified (64742-01-4)	
LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	
LD50 oral rat	≈ 2000 mg/kg bodyweight

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)	
LD50 oral rat	1689 mg/kg bodyweight (OECD 401)

Safety Data Sheet

Germ cell mutagenicity Additional information

Additional information

Carcinogenicity

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	2000 mg/kg bodyweight

Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.	
LD50 oral rat	2000 – 5000 mg/kg bodyweight
LD50 dermal rat	2000 mg/kg bodyweight

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	
LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral
	Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)

pH: Not determined

Additional information : (according to composition)

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met)

pH: Not determined

Additional information : (according to composition)

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), Reaction product

of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs..

On basis of test data. not sensitising.

This evaluation is based on the information provided by the suppliers.

Exposure may produce an allergic reaction

: Not classified (Based on available data, the classification criteria are not met)

: (according to composition)

: Not classified (Based on available data, the classification criteria are not met)

: (according to composition)

All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract,

according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)

This product contains also the following substances: Residual oils (petroleum) solvent-refined; Baseoil— unspecified; [A complex combination by hydrocarbons obtained as the solvent insoluble fraction from solvent refining of a residuum using a polar organic solvent

such as phenol or furfural. It consists of hydrocarbons having carbon numbers predominantly higher than C25 and boiling above approximately 400°C (752°F).], Distillates

(petroleum), solvent-dewaxed heavy paraffinic

this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product

must be regarded as non carcinogenic.

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

12/09/2022 (Revision date) EN (English) 15/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)	
STOT-single exposure	May cause respiratory irritation.
·	Not classified (Based on available data, the classification criteria are not met) (according to composition)

Residual oils (petroleum,) solvent-refined, Baseoil - unspecified (64742-01-4)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat
NOAEL (subacute, oral, animal/male, 28 days)	150 mg/kg bodyweight

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)	
NOAEL (oral, rat, 90 days)	3,25 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Reaction product of 1,3,4-thiadiazolidine-2,5-	dithione, formaldehyde and phenol, heptyl derivs.
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight/day

Distillates (petroleum), solvent-refined light pa	araffinic (64741-89-5)
LOAEL (oral, rat, 90 days)	= 125 mg/kg bodyweight/day (OECD TG 408)

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
LOAEL (dermal, rat/rabbit, 90 days)	100 mg/kg bodyweight/day
NOAEL (oral, rat, 90 days)	< 125 mg/kg bodyweight/day (CAS 64742-04-7, Mobil 1990) (OECD 408)
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEC (inhalation,rat, vapour, 90 days)	220 – 980 mg/m³ (Dalbey W, Osimitz T, Kommineni C, Roy T, Feuston M and Yang J 1991 - OECD 412)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)
Additional information : (according to composition)

Eni Rotra HY 80W-90	
Viscosity, kinematic	130 mm²/s (40 °C) (ASTM D 445)

12/09/2022 (Revision date) EN (English) 16/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2 Other information

Potential adverse human health effects and symptoms

Other information

: Contact with eyes may cause temporary reddening and irritation, Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, May produce an allergic reaction

: None

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.

Ecology - air

This product has a low vapour pressure. A significant exposure may happen only if the

product is used at high temperature, or in case of sprays and mists.

Ecology - water

This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)

Hazardous to the aquatic environment, short-term

: Not classified

Hazardous to the aquatic environment, long-term

(chronic)

: Toxic to aquatic life with long lasting effects.

Residual oils (petroleum,) solvent-refined, Baseoil - unspecified (64742-01-4)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	
LC50 fish 1	24 mg/l (Rainbow Trout)
LC50 fish 2	8,5 mg/l (Fathead Minnow)
EC50 Daphnia 1	91,4 mg/l
EC50 96h - Algae [1]	6,4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	15 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (acute)	1,7 – 3,3
NOEC chronic fish	3,2 mg/l (Rainbow Trout - 4d)
NOEC chronic crustacea	0,12 mg/l (Daphnia magna - 21 d)

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)	
LC50 fish 1	0,84 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 fish 2	4,21 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 Daphnia 1	0,32 mg/l Test organisms (species): Daphnia magna
EC50 Daphnia 2	0,98 mg/l Test organisms (species): Daphnia magna

12/09/2022 (Revision date) EN (English) 17/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

EC50 72h - Algae [1]	0,46 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	0,38 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	0,032 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,013 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	0,013 mg/l (21d)
NOEC chronic algae	0,01 mg/l (3d)

Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives	
LC50 fish 1	26 mg/l (LL50)
EC50 Daphnia 1	75 mg/l (EL50)
EC50 72h - Algae [1]	25 mg/l (Selenastrum capricornutum)
EC50 96h - Algae [1]	79 mg/l
NOEC chronic algae	8,1 mg/l

Mineral base oil, severely refined (light) (64741-89-5)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LC50 fish 1	> 100 mg/l (LL 50, Exxon 1995 - OECD 203)
EC50 Daphnia 1	> 10000 mg/l (EL50, Shell 1988 - OECD 202)
NOEC (acute)	≥ 100 mg/l (Pseudokirchneriella subcapitata, 72h, OECD 201 - Petro-Canada 2008)
NOEC chronic fish	≥ 1000 mg/l (Oncorhynchus mykiss, NOELR, 14d - QSAR, Redman, A. et al. 2010)
NOEC chronic crustacea	≥ 1000 mg/l (21d, OECD 211 - Shell 1994)
NOEC chronic algae	≥ 100 mg/l (Pseudokirchneriella subcapitata, 72h)

12.2. Persistence and degradability

Eni Rotra HY 80W-90	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

Residual oils (petroleum,) solvent-refined, Baseoil - unspecified (64742-01-4)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	
Biodegradation	3,6 - 7,4 % (28d - OECD 301 B)

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)	
Persistence and degradability	Readily biodegradable.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Biodegradation	66 % (28d) (OECD 301B)
Reaction product of 1.3.4-thiadiazolidine-2.5.	-dithione, formaldehyde and phenol, heptyl derivatives
Biodegradation	17,4 % (28d - Sturm test)
Mineral base oil, severely refined (light) (647	41-89-5)
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
Distillates (petroleum), solvent-dewaxed hea	vy paraffinic (64742-65-0)
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
Biodegradation	31 % (28d, Exxon 1995)
12.3. Bioaccumulative potential	
Eni Rotra HY 80W-90	
Log Pow	Not applicable for mixtures
Log Kow	Not applicable for mixtures
Bioaccumulative potential	Not established.
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	
Log Kow	5,14 (25°C)
C16-18-(even numbered, saturated and unsa	turated) alkylamines (1212780, 62-0)
Bioconcentration factor (BCF REACH)	> 500

Bioconcentration factor (BCF REACH) > 500

Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives	
Bioconcentration factor (BCF REACH)	9,4 (0,1d)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
BCF fish 1	0,4 – 6280 l/kg
BCF fish 2	3,16 – 71100 l/kg
Log Pow	1,99 – 18,02
Log Kow	Not applicable (UVCB)
Bioaccumulative potential	The test methods for this endpoint are not applicable to UVCB substances.

12.4. Mobility in soil

Eni Rotra HY 80W-90	
Mobility in soil	Not determined
Ecology - soil	No data available.

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Log Koc	1,71 – 14,7

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Ecology - soil	The test methods for this endpoint are not applicable to UVCB substances.

12.5. Results of PBT and vPvB assessment

Eni Rotra HY 80W-90

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Component		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Mineral base oil, severely refined (light) (64741-89-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

12.7. Other adverse effects

Other adverse effects : None

Additional information : No other effects known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) Waste treatment methods : Disposal must be done according to official regulations.

: Do not dispose of the product, either new or used, by discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector. Dispose of empty containers and wastes safely.

Sewage disposal recommendations

: Dispose of in a safe manner in accordance with local/national regulations. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

12/09/2022 (Revision date) EN (English) 20/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Product/Packaging disposal recommendations

: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.

Ecology - waste materials EURAL code (EWC)

: The product as it is does not contain halogenated substances.

: 13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	umber			
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping	g name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Transport document descri	iption			
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C16-18-(even numbered, saturated and unsaturated)-alkylamines; Reaction products of bis(4- methylpentan-2- yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C16-18-(even numbered, saturated and unsaturated)-alkylamines; Reaction products of bis(4- methylpentan-2- yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (C16-18-(even numbered, saturated and unsaturated)-alkylamines; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C16-18-(even numbered, saturated and unsaturated)-alkylamines; Reaction products of bis(4- methylpentan-2- yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C16-18-(even numbered, saturated and unsaturated)-alkylamines Reaction products of bis(4 methylpentan-2- yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)), 9, III
14.3. Transport hazard o	class(es)			
9	9	9	9	9
**************************************	•	**************************************		
14.4. Packing group				
III	III	III	III	III
14.5. Environmental haz	ards			
Dangerous for the environment: Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes

14.6. Special precautions for user

Overland transport

Transport regulations (ADR) : Subject to the provisions

12/09/2022 (Revision date) EN (English) 21/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Classification code (UN) : M6

Special provisions (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 90

Orange plates :

90 3082

Tunnel restriction code : EAC code : •3Z

Transport by sea

Transport regulations (IMDG) : Subject to the provisions

Special provisions (IMDG) : 274, 335, 969

Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1

: LP01, P001 Packing instructions (IMDG) Special packing provisions (IMDG) PP1 IBC packing instructions (IMDG) IBC03 Tank instructions (IMDG) T4 Tank special provisions (IMDG) TP1, TP29 EmS-No. (Fire) F-A S-F EmS-No. (Spillage) Stowage category (IMDG) Α

Air transport

Transport regulations (IATA) : Subject to the provisions

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

Inland waterway transport

Transport regulations (ADN) : Subject to the provisions

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Equipment required (ADN) : PP

Number of blue cones/lights (ADN) : 0

Rail transport

Transport regulations (RID) : Subject to the provisions

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

12/09/2022 (Revision date) EN (English) 22/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

: PP1 Special packing provisions (RID) Mixed packing provisions (RID) : MP19 Portable tank and bulk container instructions (RID) : T4 Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV Transport category (RID) 3 Special provisions for carriage – Packages (RID) : W12 : CW13, CW31

Special provisions for carriage - Loading and

unloading (RID)

Colis express (express parcels) (RID) : CE8 Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

IBC code : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

		II of the REACH Regulation (EC) No 1907/2006:
Reference code	Applicable on	Entry title or description
3(a)	Reaction product of 1,3,4-thiadiazolidine- 2,5-dithione, formaldehyde and phenol, heptyl derivs.	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched); Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.; C16-18-(even numbered, saturated and unsaturated)-alkylamines	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Eni Rotra HY 80W-90; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched); Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.; C16-18-(even numbered, saturated and unsaturated)-alkylamines	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Contains a substance on the REACH candidate list: Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs. (EC 939-460-0)

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Other information, restriction and prohibition regulations

: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et seguens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et seguens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC. Regulation EU (649/2012) - Export and Import of hazardous chemicals (PIC).

Directive 2012/18/EU (SEVESO III)

Seveso Additional information E2

15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

Finland

: Occupational Safety and Health Act No. 738/2002. Finnish National Regulations

France

Transc			
Maladies professionelles (F)			
Code	Description		
RG 36 Diseases caused by oils and fats of mineral or synthetic origin			

Germany

Employment restrictions : Employment prohibitions or restrictions on the protection of young people at work according

to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.

Water hazard class (WGK) (D) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1) WGK remark

: Classification based on the components in compliance with Verwaltungsvorschrift

wassergefährdender Stoffe (VwVwS)

Hazardous Incident Ordinance (12. BlmSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

National Rules and Recommendations : TRGS 400: Hazard assessment for activities involving Hazardous Substances

TRGS 401: Risks resulting from skin contact - identification, assessment, measures TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous

Substances: Inhalation Exposure

TRGS 555: Working instruction and information for workers

TRGS 800: Fire protection measures TRGS 900: Occupational Exposure Limits

Storage class (LGK, TRGS 510) LGK 10 - Combustible liquids

VbF class (D) : Not applicable.

Netherlands

Saneringsinspanningen : C - Minimize discharge

SZW-lijst van kankerverwekkende stoffen : None of the components are listed SZW-lijst van mutagene stoffen : None of the components are listed SZW-lijst van reprotoxische stoffen - Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen -: None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling : None of the components are listed

12/09/2022 (Revision date) EN (English) 24/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Denmark

Danish National Regulations : Young people under 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with it

Norway

Norwegian National Regulations : Working Environment Act (LOV-2005-06-17 NO. 62).

Sweden

Swedish National Regulations : This product is in compliance with Ordinance 1998:944.

Work Environment Act (1977: 1160).

Chemical Hazards in the Working Environment (AFS 2011:19).

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP] No chemical safety assessment has been carried out

A chemical safety assessment has been carried out for the following components of this mixture:

Residual oils (petroleum,) solvent-refined, Baseoil - unspecified

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.

C16-18-(even numbered, saturated and unsaturated)-alkylamines

Distillates (petroleum), solvent-refined light paraffinic

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Notes
	Revision date		
	Date of issue		
14.6	Transport regulations (ADN)	Modified	
14.6	Transport regulations (IATA)	Modified	
14.6	Transport regulations (IMDG)	Modified	
14.6	Transport regulations (RID)	Modified	
14.6	Transport regulations (ADR)	Modified	

Abbreviations and acronyms:		
	Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.	
	N/D = not available	
	N/A = not applicable	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC50	Effective concentration for 50 percent of test population (median effective concentration)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)	
LD50	Lethal dose for 50 percent of test population (median lethal dose)	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006	
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
vPvB	Very Persistent and Very Bioaccumulative	

Data sources

Training advice

Other information

- : This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
- : Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.
- : Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolunged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary. This situation is especially relevant for those operations which involve direct exposure to the vapours in the interior of tanks or other confined spaces. If this possibility is suspected, a specific assessment of inhalation risks from the presence of H2S in confined spaces must be made, to help determine prevention measures and controls (i.e. PPE) appropriate to local circumstances, and adequate emergency procedures.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
Skin Sens. 1B	Skin sensitisation, category 1B	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H335	May cause respiratory irritation.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH208	Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs May produce an allergic reaction.	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aquatic Chronic 2	H411	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.