



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL ZAHNRADSPRAY

Material number 18900

Revision date: 24.11.2023

Version: 2.3

Replaces version: 2.2

Language: en-DE

Date of print: 28.11.2023

Page: 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: AUTOL ZAHNRADSPRAY

UFI: JF11-G0P2-S00X-VGE4

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Lubricant

1.3 Details of the supplier of the safety data sheet

Company name: Eni Schmiertechnik GmbH

Street/POB-No.: Paradiesstraße 14

Postal Code, city: 97080 Würzburg

Germany

WWW: www.enischmiertechnik.de

E-mail: info.wuerzburg@eni.com

Telephone: +49 (0)931-90098-0

Telefax: +49 (0)931-98442

Department responsible for information:

Application Engineering & Product Management (AEPM)

Telephone: +49 (0)931-90098-0

E-mail: technik.wuerzburg@eni.com

1.4 Emergency telephone number

GIZ-Nord, Göttingen

Telephone: +49 (0)551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Aerosol 1; H222; H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

STOT SE 3; H336 May cause drowsiness or dizziness.

STOT RE 2; H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (CLP)



Signal word:

Danger

Hazard statements:

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H336

May cause drowsiness or dizziness.

H373

May cause damage to organs through prolonged or repeated exposure.

H412

Harmful to aquatic life with long lasting effects.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL ZAHNRADSPRAY

Material number 18900

Revision date: 24.11.2023

Version: 2.3

Replaces version: 2.2

Language: en-DE

Date of print: 28.11.2023

Page: 2 of 13

Precautionary statements:	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P260	Do not breathe mist/vapours/spray.
	P271	Use only outdoors or in a well-ventilated area.
	P312	Call a POISON CENTER/doctor if you feel unwell.
	P405	Store locked up.
	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	P501	Dispose of contents/container to hazardous or special waste collection point.

Special labelling

Text for labelling: Contains
n-Butyl acetate
Xylene
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Blend of active ingredients with propellant:



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL ZAHNRADSPRAY

Material number 18900

Revision date: 24.11.2023

Version: 2.3

Replaces version: 2.2

Language: en-DE

Date of print: 28.11.2023

Page: 3 of 13

Hazardous ingredients:

Identifiers	Designation Classification	Content
REACH 01-2119485493-29-xxxx EC No. 204-658-1 CAS 123-86-4	n-Butyl acetate Flam. Liq. 3; H226. STOT SE 3; H336. (EUH066).	< 10 %
REACH 01-2119488216-32-xxxx EC No. 215-535-7 CAS 1330-20-7	Xylene Flam. Liq. 3; H226. Acute Tox. 4; H312. Acute Tox. 4; H332. Skin Irrit. 2; H315. Eye Irrit. 2; H319. STOT SE 3; H335. STOT RE 2; H373. Asp. Tox. 1; H304. Aquatic Chronic 3; H412.	< 10 %
REACH 01-2119458049-33-xxxx list no. 919-446-0 CAS 64742-82-1	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Flam. Liq. 3; H226. STOT SE 3; H336. STOT RE 1; H372. Asp. Tox. 1; H304. Aquatic Chronic 2; H411. (EUH066).	< 10 %
EC No. 204-065-8 CAS 115-10-6	Dimethyl ether Flam. Gas 1A; H220. Press. Gas (Comp.); H280.	25 - 50 %
REACH 01-2119474691-32-xxxx EC No. 203-448-7 CAS 106-97-8	Butane Flam. Gas 1A; H220. Press. Gas (Liq.); H280.	10 - 25 %
REACH 01-2119486944-21-xxxx EC No. 200-827-9 CAS 74-98-6	Propane Flam. Gas 1A; H220. Press. Gas (Liq.); H280.	2,5 - 10 %
REACH 01-2119485395-27-xxxx EC No. 200-857-2 CAS 75-28-5	Isobutane Flam. Gas 1A; H220. Press. Gas (Liq.); H280.	< 2,5 %

Full text of H- and EUH-statements: see section 16.

Additional information: Information about Butane and Isobutane:
Contains < 0,1 % 1,3-Butadiene.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: IF exposed or concerned: Get medical advice/attention. First aider: Pay attention to self-protection!

In case of inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if problems persist.

Following skin contact: Immediately clean with water and soap followed by thorough rinsing. In case of skin reactions, consult a physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After swallowing: Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL ZAHNRADSPRAY

Material number 18900

Revision date: 24.11.2023

Version: 2.3

Replaces version: 2.2

Language: en-DE

Date of print: 28.11.2023

Page: 4 of 13

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Water spray jet, alcohol resistant foam, extinguishing powder and carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated.

May form dangerous gases and vapours in case of fire. Furthermore, there may develop: carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Heating will lead to pressure increase: Danger of bursting and explosion. Use fine water spray to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol. Avoid contact with the substance.

If possible, eliminate leakage. In case of leakage, eliminate all ignition sources. Provide adequate ventilation.

Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Keep unprotected people away.

Cordon off downwind area at risk and warn inhabitants.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion!

In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

6.4 Reference to other sections

Refer additionally to section 8 and 13.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL ZAHNRADSPRAY

Material number 18900

Revision date: 24.11.2023

Version: 2.3

Replaces version: 2.2

Language: en-DE

Date of print: 28.11.2023

Page: 5 of 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe vapour/aerosol. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation. When handling large quantities, supply emergency spray. Have eye wash bottle or eye rinse ready at work place.

Precautions against fire and explosion:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Store containers in upright position.
Storage temperature: 15 - 35 °C
Storage stability: >= 12 months

Hints on joint storage:

Keep away from food, drink and animal feedingstuffs.

Storage class:

2B = Aerosols

7.3 Specific end use(s)

No information available.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL ZAHNRADSPRAY

Material number 18900

Revision date: 24.11.2023

Version: 2.3

Replaces version: 2.2

Language: en-DE

Date of print: 28.11.2023

Page:

6 of 13

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
123-86-4	n-Butyl acetate	Europe: IOELV: STEL Europe: IOELV: TWA Germany: TRGS 900 Kurzzeit Germany: TRGS 900 Langzeit	723 mg/m ³ ; 150 ppm 241 mg/m ³ ; 50 ppm 600 mg/m ³ ; 124 ppm 300 mg/m ³ ; 62 ppm
1330-20-7	Xylene	Europe: IOELV: STEL Europe: IOELV: TWA Germany: TRGS 900 Kurzzeit Germany: TRGS 900 Langzeit	442 mg/m ³ ; 100 ppm (may be absorbed through the skin) 221 mg/m ³ ; 50 ppm (may be absorbed through the skin) 440 mg/m ³ ; 100 ppm (may be absorbed through the skin) 220 mg/m ³ ; 50 ppm (may be absorbed through the skin)
64742-82-1	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Germany: TRGS 900 Kurzzeit	100 mg/m ³ (hydrocarbons, aliphatic, C9-C14)
		Germany: TRGS 900 Langzeit	50 mg/m ³ (hydrocarbons, aliphatic, C9-C14)
115-10-6	Dimethyl ether	Europe: IOELV: TWA Germany: TRGS 900 Kurzzeit Germany: TRGS 900 Langzeit	1920 mg/m ³ ; 1000 ppm 15200 mg/m ³ ; 8000 ppm 1900 mg/m ³ ; 1000 ppm
106-97-8	Butane	Germany: TRGS 900 Kurzzeit Germany: TRGS 900 Langzeit	9600 mg/m ³ ; 4000 ppm 2400 mg/m ³ ; 1000 ppm
74-98-6	Propane	Germany: TRGS 900 Kurzzeit Germany: TRGS 900 Langzeit	7200 mg/m ³ ; 4000 ppm 1800 mg/m ³ ; 1000 ppm
75-28-5	Isobutane	Germany: TRGS 900 Kurzzeit Germany: TRGS 900 Langzeit	9600 mg/m ³ ; 4000 ppm 2400 mg/m ³ ; 1000 ppm

Biological limit values:

CAS No.	Designation	Type	Limit value	Parameter	Sampling
1330-20-7	Xylene	Germany: TRGS 903, urine	2000 mg/L	Methylhippur-(Tolur-)säure (alle Isomere)	end of exposure or end of shift

8.2 Exposure controls

Provide good ventilation and/or an exhaust system in the work area.

Personal protection equipment

Occupational exposure controls

Respiratory protection:	Respiratory protection must be worn whenever the WEL levels have been exceeded. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.
Hand protection:	Protective gloves according to DIN EN 374. Glove material: nitrile rubber Breakthrough time: > 480 min Layer thickness: 0,4 mm Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Eye protection:	Tightly sealed goggles according to DIN EN ISO 16321-1:2022.
Body protection:	Flame retardant, antistatic and chemical resistant protective clothing.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL ZAHNRADSPRAY

Material number 18900

Revision date: 24.11.2023

Version: 2.3

Replaces version: 2.2

Language: en-DE

Date of print: 28.11.2023

Page: 7 of 13

General protection and hygiene measures:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapour/aerosol.
Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.
Do not get in eyes, on skin, or on clothing.
When using do not eat or drink. Contaminated work clothing should not be allowed out of the workplace.
Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse.
Have eye wash bottle or eye rinse ready at work place.
When handling large quantities, supply emergency spray.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	gaseous
Colour:	Form: Aerosol black
Odour:	Ester-like
Odour threshold:	No data available
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	-44 °C
Flammability:	Extremely flammable aerosol.
Upper/lower flammability or explosive limits:	LEL (Lower Explosion Limit): 1,50 Vol-% UEL (Upper Explosive Limit): 18,60 Vol-%
Flash point/flash point range:	Not applicable
Auto-ignition temperature:	235 °C
Decomposition temperature:	No data available
pH:	Not applicable
Viscosity, kinematic:	No data available
Water solubility:	Slightly miscible
Partition coefficient: n-octanol/water:	No data available
Vapour pressure:	No data available
Density:	at 20 °C: 0,752 g/mL
Vapour density:	No data available
Particle characteristics:	Not applicable

9.2 Other information

Explosive properties:	Vapours can form explosive mixtures with air. Exposure to temperatures exceeding 50 °C will increase pressure: resulting in danger of bursting or explosion.
Oxidizing characteristics:	No data available
Auto-ignition temperature:	Not self-igniting
Solvent content:	22,9 %
Solid content:	30,3 %
Evaporation rate:	No data available
Additional information:	Pressure 20 °C : 3-6 bar



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL ZAHNRADSPRAY

Material number 18900

Revision date: 24.11.2023

Version: 2.3

Replaces version: 2.2

Language: en-DE

Date of print: 28.11.2023

Page: 8 of 13

SECTION 10: Stability and reactivity

10.1 Reactivity

Extremely flammable aerosol.
Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.
storage stability: >= 12 months

10.3 Possibility of hazardous reactions

Pressurised container: May burst if heated.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

No dangerous reactions with proper and specified storage and handling

Thermal decomposition:

No data available

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects:

The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Mild irritant

Serious eye damage/irritation: Based on available data, the classification criteria are not met. Mild irritant

Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.

Skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): STOT SE 3; H336 = May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure): STOT RE 2; H373 = May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard: Asp. Tox. 1; H304 = May be fatal if swallowed and enters airways.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL ZAHNRADSPRAY

Material number 18900

Revision date: 24.11.2023

Version: 2.3

Replaces version: 2.2

Language: en-DE

Date of print: 28.11.2023

Page: 9 of 13

11.2 Information on other hazards

Endocrine disrupting properties: No data available

Other information:

Information about n-Butyl acetate:

LD50, Rat, oral: 10.760 mg/kg (OECD 423)

LD50, Rabbit, dermal: 14.112 mg/kg (OECD 402)

LC50, Rat, inhalative: 0,74 mg/L (OECD 403)

Information about Xylene:

LD50, Rat, oral: 3.523 mg/kg

LD50, Rabbit, dermal: 12.126.000 mg/kg

LC50, Rat, inhalative: 21.124 mg/m³

Information about Dimethyl ether:

LC50, Rat, inhalative: 309 mg/L

Information about Butane:

LC50, Rat, inhalative: 1.443 mg/L/15min

Information about Propane:

LC50, Rat, inhalative: > 20 mg/L

Information about Isobutane:

LC50, Rat, inhalative: > 20 mg/L

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Harmful to aquatic life with long lasting effects.

Information about Xylene:

Fish toxicity: LC50: 2,6 mg/L/96h

Daphnia toxicity: EC50: 1 mg/L/24h

Algae toxicity: EC50: 0,44 mg/L/72h

Water Hazard Class:

2 = obviously hazardous to water (Self-classification (mixture).)

12.2 Persistence and degradability

Further details:

No data available

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

General information:

Do not allow to enter into ground-water, surface water or drains.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL ZAHNRADSPRAY

Material number 18900

Revision date: 24.11.2023

Version: 2.3

Replaces version: 2.2

Language: en-DE

Date of print: 28.11.2023

Page: 10 of 13

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 16 05 04* = Gases in pressure containers (including halons) containing hazardous substances/Aerosol
* = Evidence for disposal must be provided.

Recommendation: Do not pierce or burn, even after use.
Special waste. Dispose of waste according to applicable legislation.
Do not dispose of with household waste.

Package

Waste key number: 15 01 04 = metallic packaging
Recommendation: Dispose of waste according to applicable legislation.
Empty carefully and completely, if possible. Handle empty containers with care. Incineration may cause explosion.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID, ADN, IMDG, IATA-DGR:
UN 1950

14.2 UN proper shipping name

ADR/RID, ADN, IMDG: UN 1950, AEROSOLS
IATA-DGR: UN 1950, AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

ADR/RID, ADN: Class 2, Code: 5F
IMDG: Class 2.1, Subrisk -
IATA-DGR: Class 2.1



14.4 Packing group

ADR/RID, ADN, IATA-DGR: not applicable
IMDG: -

14.5 Environmental hazards

Dangerous for the environment: Substance/mixture is not environmentally hazardous according to the criteria of the UN model regulations.

Marine pollutant - IMDG: no

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board: RID: Kemmler-number 23, UN number UN 1950
Hazard label: 2.1
Special Provisions: 190 327 344 625
Limited quantities: 1 L
EQ: E0
Package - Instructions: P207 LP200
Package - Special Provisions: PP87 RR6 L2
Special provisions for packing together: MP9
Tunnel restriction code: (D)
Remarks: ADR/RID: Transport as "limited quantity" according to chapter 3.4 ADR/RID (> 8.000 kg total gross mass): Tunnel restriction code (E)



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL ZAHNRADSPRAY

Material number 18900

Revision date: 24.11.2023

Version: 2.3

Replaces version: 2.2

Language: en-DE

Date of print: 28.11.2023

Page: 11 of 13

Inland waterway craft (ADN)

Hazard label: 2.1
Special Provisions: 190 327 344 625
Limited quantities: 1 L
EQ: E0
Equipment necessary: PP - EX - A
ventilation: VE01,VE04

Sea transport (IMDG)

EmS: F-D, S-U
Special Provisions: 63 190 277 327 344 381 959
Limited quantities: 1000 mL
Excepted quantities: E0
Package - Instructions: P207, LP200
Package - Provisions: PP87, L2
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: SW1 SW22
Segregation: SG69
Properties and observations: -
Segregation group: none

Air transport (IATA)

Hazard label: Flamm. gas
Excepted Quantity Code: E0
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special Provisions: A145 A167 A802
Emergency Response Guide-Code (ERG): 10L

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Germany

Storage class: 2B = Aerosols
Water Hazard Class: 2 = obviously hazardous to water (Self-classification (mixture).)
Incident regulation: Richtlinie 2012/18/EU (Seveso III);
Physikalische Gefahren: Ziffer 1.2.3.1 = Code P3a, Mengenschwelle 150 000kg / 500 000kg
Technical guidance air: 5.2.5
Class NK: 49,5 %
Information on working limitations:
Observe employment restrictions for young people.
Observe employment restrictions for expectant or nursing mothers.
Further regulations, limitations and legal requirements:
No data available

National regulations - EC member states

Volatile organic compounds (VOC):
69,7 % by weight



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL ZAHNRADSPRAY

Material number 18900

Revision date: 24.11.2023

Version: 2.3

Replaces version: 2.2

Language: en-DE

Date of print: 28.11.2023

Page: 12 of 13

Further regulations, limitations and legal requirements:

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances
[Seveso-III-Directive] refer to Germany, 12. BImSchV

Use restriction according to REACH annex XVII, no.: 3, 40, 75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances
[Seveso-III-Directive]: P3a

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Wording of the H-phrases under paragraph 2 and 3:

H220 = Extremely flammable gas.

H222 = Extremely flammable aerosol.

H226 = Flammable liquid and vapour.

H229 = Pressurised container: May burst if heated.

H280 = Contains gas under pressure; may explode if heated.

H304 = May be fatal if swallowed and enters airways.

H312 = Harmful in contact with skin.

H315 = Causes skin irritation.

H319 = Causes serious eye irritation.

H332 = Harmful if inhaled.

H335 = May cause respiratory irritation.

H336 = May cause drowsiness or dizziness.

H372 = Causes damage to organs through prolonged or repeated exposure.

H373 = May cause damage to organs through prolonged or repeated exposure.

H411 = Toxic to aquatic life with long lasting effects.

H412 = Harmful to aquatic life with long lasting effects.

EUH066 = Repeated exposure may cause skin dryness or cracking.

Reason of change: Changes in section 14: ADR/RID

Date of first version: 25.11.2021

Department issuing data sheet: see section 1: Department responsible for information



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

AUTOL ZAHNRADSPRAY

Material number 18900

Revision date: 24.11.2023

Version: 2.3

Replaces version: 2.2

Language: en-DE

Date of print: 28.11.2023

Page: 13 of 13

Abbreviations and acronyms:

- Acute Tox.: Acute toxicity
- ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- Aerosol: Aerosol
- Aquatic Chronic: Hazardous to the aquatic environment - chronic
- AS/NZS: Australian Standards/New Zealand Standards
- Asp. Tox.: Aspiration toxicity
- CAS: Chemical Abstracts Service
- CFR: Code of Federal Regulations
- CLP: Classification, Labelling and Packaging
- DMEL: Derived minimal effect level
- DNEL: Derived no-effect level
- EC: European Community
- EC50: Effective Concentration 50%
- EN: European Standard
- EQ: Excepted quantities
- EU: European Union
- Eye Irrit.: Eye irritation
- Flam. Gas: Flammable gases
- Flam. Liq.: Flammable liquid
- IATA: International Air Transport Association
- IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
- IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
- IMDG Code: International Maritime Dangerous Goods Code
- LC50: Median lethal concentration
- LD50: Lethal dose 50%
- LEL: Lower Explosion Limit
- MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
- OECD: Organisation for Economic Co-operation and Development
- OEL: Occupational Exposure Limit Value
- OSHA: Occupational Safety and Health Administration
- PBT: Persistent, bioaccumulative and toxic
- PNEC: Predicted no-effect concentration
- Press. Gas: Gases under pressure
- REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
- RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
- Skin Irrit.: Skin irritation
- STOT RE: Specific target organ toxicity - repeated exposure
- STOT SE: Specific target organ toxicity - single exposure
- TLV: Threshold Limit Value
- TRGS: Technical Rules for Hazardous Substances
- UN: United Nations
- vPvB: Very persistent and very bioaccumulative
- WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

Most recent product information is available at:
<http://sumdat.net/19kwiz9>

